

# AirWay

## Wireless Signal Transceiver

### Why install AirWay?

Advanced data loggers require one or more input signals from existing instrumentation or additional sensors. It is not always possible or practicable to physically connect these signals using traditional cabling.

AirWay is an electronic device that wirelessly transmits and receives up to 4 input/output control signals. It can be used to provide remote I/O via HoistNet for products such as Liftlog™ or Liftlog XL data logger, where the desired signals cannot be cabled into the logger directly. Alternatively, two AirWay units can be used together to provide up to 4 virtual connections.

### Technical Details



#### PHYSICAL

Dimensions (mm): 160 x 110 x 40mm  
Operating temperature range (°C): -20 to 65

#### ELECTRICAL

Supply Voltage: 32-240VAC  
Max power consumption: 0.5W  
Connections: 4 inputs, 4 outputs  
Signal range: 500m



**HoistNet**

### About CASWA

CASWA is an Australian company that designs electronics and software for collecting, analysing and disseminating data to help asset owners and maintainers make better business decisions. CASWA also manufactures and distributes the Sole Digital range of asset management products at a facility in Perth, Western Australia, many of which have been developed specifically to support the crane industry.

More information on the AirWay Wireless Signal Transceiver is available from [www.soledigital.com.au/AirWay.html](http://www.soledigital.com.au/AirWay.html) or contact us directly at:

2/33 Horus Bend, Bibra Lake, WA 6163

P: +61 8 9277 0900 | F: +61 8 9467 0550 | E: [info@caswa.com](mailto:info@caswa.com) | W: [www.caswa.com](http://www.caswa.com)